

LIPOD LITE

Light Weight and Affordable 3D Scanner





LiPod Lite by GreenValley International makes terrestrial 3D laser scanning (TLS) easier and more affordable than ever before. Its compact and lightweight design makes this high accuracy LiDAR surveying solution easy to transport and operate. LiPod allows users to quickly survey large interior and exterior sites without the need for inserting registration targets.

Lightweight Design

The device weighs only 3.0 kg (6.6 lbs) and is equipped with a carbon fiber tripod.

Cost-effective Reliability

The widely adopted VLP-16 sensor from Velodyne LiDAR powers this accurate 3D laser scanning system at an attractive price.

Wireless Control

Connect to and control the system from any WiFienabled device. No cables required.

Automatic Leveling

An integrated high-precision, dual-axis compensator allows users to save time leveling the device at each scanning location.

Multi-Sensor Integration

The multiple sensor design with a panoramic camera makes the LiPod more than just a simple 3D laser scanner.

Full Solutions

Build seamless workflows using various pre and postprocessing software solutions from GVI to satisfy the needs for various industries.

Specifications

| System Specifications | | | | |
|------------------------------------|-----------------------|---|-----------------------|--|
| Dimensions [1] (mm) | 150*375mm | Battery | 5700mAh | |
| Weight [1] (Excl. Battery) | 3.0 kg | Battery Life | ~4 h / Battery | |
| Storage Capacity | 128 GB SSD | Ports | USB, Network | |
| Suitable Environment | Indoor and Outdoor | Processor | 2 Cores and 4 Threads | |
| System Control and Data Display | Wireless Mode | Smartphone/Tablet Connect via WIFI, Simultaneous Control and Display | | |
| | Wireless Mode | Wire Connection between System and Tablet, Control and Data Transmission | | |
| Data Output | | | | |
| Relative Accuracy | ≤3cm ^[2] | Absolute Accuracy | ≤5cm ^[2] | |
| Point Cloud Data Format | las, laz, ply, LiData | | | |

| Sensor Specifications | | | | |
|-----------------------|------------------|----------------|---------|--|
| Laser Sensor | VLP16 | Range Accuracy | ±3 cm | |
| Verticle FOV | -15°~ 15° | Horizontal FOV | 0°~360° | |
| Maximum Range | 100 m | | | |
| Camera Specification | | | | |
| Camera | Panoramic Camera | Resolution | 18 MP | |
| Sensor Size | 1 inch | | | |

[1] The camera module and GNSS module are optional, the weight and dimension of the system may vary depending on the choice of modules.

 $\label{eq:continuous} \ensuremath{\text{[2]}} \ensuremath{\text{May}} \ensuremath{\text{be}} \ensuremath{\text{affected}} \ensuremath{\text{by}} \ensuremath{\text{environmental}} \ensuremath{\text{and}} \ensuremath{\text{route}} \ensuremath{\text{planning}} \ensuremath{\text{factors}}.$







