

GreenValley International

LIAIR X3-H



Enhanced Lightweight UAV LiDAR System

LiAir X3-H is the newest compact, high-performance unit in the LiAir series by GreenValley International. It adopts a new integrated design style and integrates lightweight LiDAR, self-developed inertial navigation, a high-resolution mapping camera and on-board computer systems providing new levels of efficiency.

Advantages

I Lightweight & Simple

Integrated simple yet rugged design, allowing for protection against the elements with an IP64 rating. The operation interface is straightforward, allowing one touch operation for maximum efficiency.

I New Camera, providing ultra-clear picture quality

Built-in new high-resolution custom mapping camera, the image resolution is upgraded from 24 Megapixels to 26 Megapixels, allowing for high-quality true-color point clouds as well as orthophotos for Photogrammetry.

LiPlan Flight Assistance Software, making field work easy

LiPlan supports real-time point cloud display, parameter adjustment, and status monitoring. It can be directly installed on the M300 RTK remote controller and used in conjunction with the X3-H to help operators control the site conditions in real time.



Specifications

| System Parameters | | | |
|---|--|----------------------------|------------------------------------|
| Detection Range | 190m @ 10% reflectance 450m @ 80% reflectance | System Accuracy (Vertical) | 5cm @ 70m |
| Dimensions | 136*106*129mm | Typical Flight Speed | 5-10 m/s |
| Weight | 1.25kg | Internal Storage | 256G TF Card |
| Voltage | 12~24V, 0.9A @ 24VDC | Power Consumption | 22W |
| Operating Temperature | -20~50°C | Storage Temperature | -30~60°C |
| LiDAR Sensor Technical Para | ameters | | |
| Wavelength | 905nm | Laser Class | Class1 |
| Range Accuracy | 2cm (1σ@20m) | FOV | 70.4°(Horizontal) ×4.5° (Vertical) |
| Scan Rate | 720,000 points/s (Triple return) | Returns | Up to 3 returns |
| Scan Method | Repetitive Scan | | |
| Inertial Navigation System | | | |
| GNSS | GPS, GLONASS, BeiDou | Azimuth Accuracy | 0.038° |
| Attitude Accuracy | 0.008° | IMU Data Frequency | 200HZ |
| Camera | | | |
| Image Sensor | APS-C | Pixels | 26 Megapixels |
| Focal Length | 16mm/24mm | Image Size | 6252 x 4168 |
| Software | | | |
| Post-Processing | LIDAR360 | Pre-Processing | LiGeoreference |
| Flight Planning and Control Software | LiPlan | | |



2120 University Ave, Berkeley, CA, USA 94704 I www.greenvalleyintl.com I info@greenvalleyintl.com